

AC-2100/2100H

IPX3 Dust/Water Resistance / Anti-Passback



Features



Patented Live & Fake Finger Detection
- Optical sensor and algorithm detect fake fingers (paper, film, silicone, rubber and gelatin)



Local Anti-Passback
- Compatible with a slave reader SR-100FP



IPX3 Dust/Water Resistance
- Outdoor installation



USB Memory Slot
- Quick upload and download

Specification

CPU	RISC 266MHz, 32bit CPU	Memory	8MB SD RAM + 4MB Flash
LCD	128 x 64 Graphic LCD	Max Users	100/1,500
Communication	TCP/IP, RS-485, RS-232, Wiegand In & Out, WiFi (Optional)	Log Capacity	5,000
Dimension	93 x 170 x 40 mm	Certificates	CE, FCC, RoHS
RFID Card Option	125KHz EM / 13.56MHz Mifare / Desfire		



RS485 Fingerprint & Card Slave Reader

SR-100FP

RFID Card Option
125KHz EM / Mifare / DESFire

◆ Features



Patented Live & Fake Finger Detection
- Optical sensor and algorithm detect fake fingers (paper, film, silicone, rubber and gelatin)



Slave Reader
Compatible with AC-2100 / 2100H

System Architecture with Fingerprint Terminals (AC-2100)

◆ Anti-Passback

